

CBIA 2016 Forum

High R-Value Wall Sheathing

Total Wall Platinum
R-Tech Platinum
InsulFoam CI Platinum





InsulFoam Platinum Series

 Based on "Neopor" a new resin technology from BASF.









Total Wall Platinum

- Designed for Stucco systems
- Is a vapor permeable weather resistive barrier w/ Polygard 136 RT tape.
- Promotes better hydration of the one coat stucco for less cracking.
- Available in 2x8 and 4x8 T&G.
- Standard 1" thickness also available in ½" for use over shear walls and gables.





ASTM C1363 vs C518

- Whole wall system test that includes temperature differential, wind and overall assembly performance vs materials between a hot and cold plate. Closer to real world.
- Takes into account benefits of continuous insulation and air barriers.
- Addresses convection, conduction and infrared performance of an assembly.







Total Wall Platinum Comparative C1363

Base wall ½" gyp, 2x4,
 R13 FG, air barrier
 R-12.8





- Standard 1.5 pcf T&G on base wall R-17.3
- Total wall Platinum in lieu of std. T&G R-20.9



An increase of 8.1 over the base wall







R-Tech Platinum Comparative C1363

- R-Tech Platinum
 Sheathing 1" adds R-8
- Water vapor permeable WRB w/ Polygard 136 RT
- ½" available. Adds R-4.
- Fits standard window and door profiles.
- Can be used over shear wall sheathing.

- Base wall ½" gyp, 2x6, R19 FG, air barrier R-19.7
- Add R-Tech Platinum sheathing R-27.7

An increase of 8.0 over the base wall








InsulFoam CI Platinum

- Thickness of 2"
- Uses standard gun fired 16d nails
- Provides attachment surface 7/16 OSB
- Continuous Insulation of R- 9 while providing shear component.







CIBA

High R-Value Wall Sheathing

??Questions??





